

NUMBER: DELH21013389-E

DATE : 28<sup>TH</sup> SEP, 2021



ORIGINAL SAMPLE





NUMBER: DELH21013389-E

DATE : 28<sup>TH</sup> SEP, 2021

APPLICANT: ALL TIME PLASTICS PVT.LTD.

PLOT NO. 377/1/1&2), KACHIGAM, CHAR RASTA, DAMAN - 396210

ATTN: ZARIR PATEL

**SAMPLE DESCRIPTION** : CANISTER CA 001 (750 ML) (36 PC PK) (CHEVRON DESIGN)

DATE RECEIVED : 25<sup>TH</sup> JULY, 2021

BUYER'S NAME : BUYING AGENT/ CONTACT : --

 ITEM CODE
 : 407136-36

 HSN CODE
 : 39241090

 BARCODE
 : 8902084071360

 COLOR
 : WHITE

END USE : -COUNTRY OF ORIGIN : -COUNTRY OF DESTINATION : --

MANUFACTURER'S NAME : ALL TIME PLASTICS PVT. LTD.

**TESTS CONDUCTED:** AS PER THE REQUEST BY THE APPLICANT. FOR FURTHER DETAILS PLEASE

REFER TO THE ENCLOSED PAGE (S).

### **CONCLUSION:**

TESTED SAMPLE	<u>STANDARD</u>	RESULT
	TOTAL LEAD CONTENT (WITH REFERENE TO REGULATION (EC) NO. 1907/2006 (REACH) AND ITS AMENDMENTS, ANNEX XVII, ENTRY 63)	М
	TOTAL CADMIUM CONTENT  (AS PER EC NO. 1907/2006 (REACH) AND ITS AMENDMENTS,  ANNEX XVII, ENTRY 23)	М
	BISPHENOL-A CONTENT TEST (BY SOLVENT EXTRACTION FOLLOWED BY LC-MS / MS)	М
	OVERALL MIGRATION (IS 9845)	М
	SPECIFIC MIGRATION OF HEAVY METALS (IS 9845)	М
SUBMITTED SAMPLE	SPECIFIC MIGRATION OF PHTHALATES (SOLVENT EXTRACTION FOLLOWED BY GC-MSD ANALYSIS)	М
	<b>DISHWASHER SAFE TEST</b> (AS PER IN-HOUSE TEST METHOD)	М
	MICROWAVE SAFE TEST (IN-HOUSE TEST METHOD)	М
	FREEZER SAFE TEST (IN-HOUSE TEST METHOD)	М
	RESISTANCE TO CORROSION TEST (ISO 9227: 2017)	#

(n)

Page 2 of 8



NUMBER: DELH21013389-E

DATE : 28<sup>TH</sup> SEP, 2021

NOTE: M = MEET CLIENT'S REQUIREMENT

# = NO SPECIFIED REQUIREMENT

F = BELOW CLIENT'S REQUIREMENT

N/A = NOT APPLICABLE

FOR INTERTEK INDIA PVT. LTD

**SANJAY SADANA** 

Intertek India Pvt. Ltd.

Stodame

**TECHNICAL MANAGER - HARDLINE** 



Tel: 0124-4503400,

Fax: 0124-4303592

www.Intertek.com



NUMBER: DELH21013389-E

DATE : 28<sup>TH</sup> SEP, 2021

### **TEST CONDUCTED:**

### 1. TOTAL LEAD CONTENT IN SUBSTRATE

TEST REGULATION: WITH REFERENCE TO EC NO. 1907/2006 (REACH) AND ITS AMENDMENTS, ANNEX XVII, ENTRY 63

TEST METHOD: ANALYSIS WAS PERFOMRED BY ICP-MS/AAS

TESTED SAMPLE	RESULT (ppm)	CLIENT'S REQUIREMENT
SUBMITTED SAMPLE	WHITE PLASTIC: <10PPM	< 500 PPM

**REMARK:** ND = NOT DETECTED

DETECTION LIMIT = 10 PPM

\*REQUIREMENT IS REFERED FROM REACH ANNEX XVII, ENTRY 63

#### 2. TOTAL CADMIUM CONTENT IN SUBSTRATE

TEST REGULATION: EC NO. 1907/2006 (REACH) AND ITS AMENDMENTS, ANNEX XVII, ENTRY 23 TEST METHOD: WITH REF. TO EN112-ANALYSIS WAS PERFOMRED BY ICP-MS/AAS

TESTED SAMPLE	RESULT (ppm)	CLIENT'S REQUIREMENT
SUBMITTED SAMPLE	WHITE PLASTIC: <10PPM	<100 PPM

**REMARK:** ND = NOT DETECTED

DETECTION LIMIT = 10 PPM

\*REQUIREMENT IS REFERED FROM REACH ANNEX XVII, ENTRY 23

#### 3. BISPHENOL-A CONTENT TEST:

(BY SOLVENT EXTRACTION FOLLOWED BY LC-MS / MS)

(			
TESTED COMPONENT	<u>RESULTS</u>	CLIENT'S REQUIREMENT	
SUBMITTED SAMPLE	<b>COMPLIES</b> WHITE PLASTIC: ND	SHALL NOT CONTAIN ANY DETECTABLE LEVELS OF BISPHENOL A (BPA)	

**DETECTION LIMIT: 0.1 PPM** 

Intertek India Pvt. Ltd.





NUMBER: DELH21013389-E

: 28<sup>TH</sup> SEP, 2021 DATE

### 4. OVERALL MIGRATION TEST:

TEST METHOD: IS 9845

### **TEST CONDITIONS AND RESULTS:**

MATERIAL PUT	SIMULANT	TEST CONDITION	RESULT IN (mg/dm <sup>2</sup> )	MAX. LIMIT
INTO CONTACT	USED	TEST CONDITION	[1]	(mg/dm <sup>2</sup> )
SUBMITTED SAMPLE	N-Heptane	38°C FOR 30 MIN.	<5	<10

**REMARK:** <= LESS THAN

RESULTS ARE GIVEN IN mg/dm<sup>2</sup>= Milligram per decimeter square

### **TESTED COMPONENT:**

1. CANISTER

#### 5. SPECIFIC MIGRATION OF HEAVY METALS TEST:

TEST METHOD: IS 9845

TEST CONDITION: 3% ACITIC ACID AT 40°C FOR 10 DAYS

ELEMENT	RESULTS (mg/kg) [1]	MAX. PERMISSIBLE LIMIT — (mg/kg)
Barium (Ba)	<0.1	1.0
Cobalt (Co)	<0.01	0.10
Copper (Cu)	<1.0	5.0
Iron (Fe)	<5.0	48.0
Lithium (Li)	<0.1	0.6
Manganese (Mn)	<0.1	0.6
Zinc (Zn)	<1.0	25.0
Antimony (Sb)	<0.02	0.04

<sup>=</sup> LESS THAN

mg/kg = MILLIGRAM PER KILOGRAM

## **TESTED COMPONENT:**

1. CANISTER

Intertek India Pvt. Ltd.





NUMBER: DELH21013389-E

: 28<sup>TH</sup> SEP, 2021 DATE

## 6. SPECIFIC MIGRATION OF PHTHALATE:

SOLVENT EXTRACTION FOLLOWED BY GC-MSD ANALYSIS

TEST CONDITION: 3% ACITIC ACID AT 40°C FOR 10 DAYS.

	RESULT (PPM)
TESTED COMPONENTS	[1]
DIBUTYL PHTHALATE (DBP)	ND
DIETHYL HEXYL PHTHALATE (DEHP)	ND
BENZYL BUTYL PHTHALATE (BBP)	ND
DI-ISO-NONYL PHTHALATE (DINP)	ND
DI-N-OCTYL PHTHALATE (DnOP)	ND
DI-ISO-DECYL PHTHALATE (DIDP)	ND

Limit: Individual Less than 0.1% (1000 ppm)

### **TESTED COMPONENT:**

1. CANISTER

## 7. DISHWASHER SAFE TEST:

REFERENCE: IN-HOUSE TEST METHOD

### **TESTING CONDITIONS:**

Intertek India Pvt. Ltd.

(1) SELECTED CYCLE: NORMAL

(2) CYCLE DURATION: 120 MINUTES (APROX.) (3) TEMPERATURE CONDITION: 60°C (APROX.)

(4) DETERGENT USED: CASCADE (5) NO. OF CYCLES: 10 CYCLES

TESTED SAMPLE	<u>OBSERVATION</u>	REQUIREMENT
SUBMITTED SAMPLE	<b>COMPLIES</b> NO VISUAL CHANGE OBSERVED	SHALL NOT SHOW ANY CHIPPING, CRACKING, GLAZE CRAZING OR OTHER VISUAL CHANGE IN APPEARANCE.



Tel: 0124-4503400,

Fax: 0124-4303592

www.Intertek.com



NUMBER: DELH21013389-E

DATE : 28<sup>TH</sup> SEP, 2021

## 8. MICROWAVE SAFE TEST:

(IN-HOUSE TEST METHOD)

MICROWAVE SAFE EVALUATION:

TESTED SAMPLE	OBSERVATION	REQUIREMENT
SUBMITTED SAMPLE	COMPLIES	SHALL NOT SHOW ANY CRACKING/CRAZING, MELTING, DEFORMATION OR OTHER UNUSUAL CHANGES. TEMPRATURE OF HANDLE OR SURFACE SHALL NOT EXCEED THE FOLLOWING LIMITS. Ceramic, Glass-Ceramic or Glass: 56°C Plastic: 60°C

### 9. FREEZER SAFE TEST:

(IN-HOUSE TEST METHOD)

## **TESTING CONDITIONS:**

Intertek India Pvt. Ltd.

(1) FREEZER TEMPERATURE: -18°C

(2) FREEZER EXPOSED PERIOD: 24 HOURS

TESTED SAMPLE	OBSERVATION	REQUIREMENT
SUBMITTED SAMPLE	COMPLIES	SHALL NOT SHOW ANY CRACK/DAMAGE/DEFORMATI ON





NUMBER: DELH21013389-E

DATE : 28TH SEP, 2021

### **10. SALT SPRAY TEST**:

(ISO 9227: 2017)

- (1) SODIUM CHLORIDE (NaCl) SOLUTION CONCENTRATION = 50 gm/litre
- (2) pH = 6.8
- (3) CHAMBER TEMPERATURE = 35°C
- (4) EXPOSURE PERIOD = 24 HOURS

TESTED COMPONENT	RESULT	REQUIREMENT
SUBMITTED SAMPLE (LID PART)	<b>GRADE: 10</b> (NO VISUAL CHANGE OBSERVED)	NOT PROVIDED

AREA OF DEFECTS A (%)	RATING
NO DEFECTS	10
$0 < A \le 0.1$	9
$0.1 < A \le 0.25$	8
$0.25 < A \le 0.5$	7
$0.5 < A \le 1.0$	6
$1.0 < A \le 2.5$	5
$2.5 < A \le 5.0$	4
$5.0 < A \le 10$	3
$10 < A \le 25$	2
$25 < A \le 50$	1
A > 50	0

### # END OF TEST REPORT #

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct.

Tel: 0124-4503400,

Page 8 of 8

Intertek India Pvt. Ltd.